



TUFTEX[®]

POLY-LITE[™] & RIDGE-LITE[™]

Skylight Panels • Sidelight Panels



***Here Comes
the Sun!***



Polycarbonate Skylight and Sidelight Panels for Metal Buildings

Benefits

- **Brings Natural Light into Buildings**
- **Retains Optical Clarity . . . Will Not Yellow Like Fiberglass**
- **Up to 20 Times Stronger than Fiberglass**
- **100% UV Protection**
- **Withstands Extreme Temperatures (-40°F to +270°F)**
- **Hail and Wind Resistant**
- **Best Snow Load Capacity**
- **Saves Electricity**
- **Ten Year Limited Warranty**
- **Matches the Most Popular Metal Roofing Profile**



Poly-Lite™ Specifications

Panel Width:	38" U.S. Standard
Span:	2' On Center
Corrugation Height:	3/4"
Panel Length:	8', 10', 12', 16'
Panel Thickness:	.032"
Weight:	.69 lbs/ft
Fasteners Per Panel:	Every Six Inches
Colors:	Clear - 90% Light Transmission (8', 10', 12', 16') Smoke - 80% Light Transmission (8', 12')

Pallet: 200 Pieces

Panels Packaged in Bundles of 10
Freight Prepaid on Orders of 100 Panels

